### **Built-in Flex Fireplaces**



# Flex 68BY





ecosmartfire.com

### **Built-in Flex Fireplaces**



# Flex Bay Design features





Jerry Can with Safety Spout & e-NRG bottle adaptor



#### **Lighting Rod & Lighter**



XL Baffles (XL Burners Only)



**Black Glass Charcoal\*** 



**Glass Fire Screen/s** 

#### **Optional Accessories**



Decorative Steel Logs\*

Disclaimer, All product specifications and data are subject to change without notice and believed to be correct at the time of publication. MAD Design Group (MDG), its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "MAD Design Group"), disclaim any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify MDG's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of MDG. Customers using or applications. Images are indicative ony.

#### 1. Zero Clearance

Self-contained, zero clearance construction allows your Flex fireplace to be framed into wood or metal studs, providing installation freedom and flexibility for builders, architects, interior designers, landscapers and homeowners.

#### 2. Decorative Side Box

Customise your fireplace design with a decorative box placed on one or more sides, and fill with your chosen noncombustible accessory.

#### **Built to Last a Lifetime**

Zinc sealed steel construction powder coated with super hi-temp black paint prevents rusting so all fireplaces can be used both indoors or outdoors.

#### Quick and Easy Installation

Requiring virtually no assembly, Flex Fireplaces are designed to be placed into the desired location, safely secured into position, and operated immediately.

## 3. Glass Fire Screen/s

The toughened glass fire screen stabilises the flame in windy conditions. The Integrated windscreen sits flush behind the frame.

#### **No Connections**

Light up outdoor spaces with a soft, alluring glow - easily and efficiently, without cumbersome connections.

#### 4. Colours

Available in a timeless black finish, Flex Fireplaces come with Stainless Steel or Black burners.



© Copyright 2004 - 2022 MAD Design Group. All rights reserved. V0622

5. Single Room Application

Bay fireplaces feature three open sides - view the flame

from the front and both sides.

No Flue, No Chimney, No Vent

Fuelled by clean-burning e-NRG

bioethanol, our burners produce

a beautiful orange flame without

any smoke, soot or ash.

**Forefront of Fireplace** 

Backed by 17 years of

research and development,

and third-party certification,

fuel ignition technologies.

These models comply with existing standards in the USA, Europe, UK and Australia. O-TL

Certified and ACCC Safety

\*Decorative media is not to be placed

directly on top of the burner or anywhere they can interfere with the operation of the

listed to UL1370, EN 16647 BSI

**Global Compliance** 

Mandate compliant.

burner or the stability of flame.

each model in the Flex series

features world-class safety and

Technology



# Flex 68BY Specifications

Burner Ventilation and Efficiency*					Construction			
			<b>†</b>				$\longleftrightarrow$	
Flex Model	Compatible Burner	Fuel Capacity	Heats on Average (Indoors)	Approx. Burn Time	Minimum Room Size	Viewing Area Size	Minimum Wall Length	
68BY	XL1200	10 L [2.6 Gals]	Over 65 m² [700 ft²]	9 - 14 hours	115 m³ [4,061 ft³]			
68BY.BXL 68BY.BXR	XL900	9 L [2.4 Gals]	Over 60 m² [645 ft²]	8 - 13 hours	110 m³ [3,884 ft³]	1,730mm [68in]	1,935mm [76in]	
68BY.BX2	XL500	5 L [1.3 Gals]	Over 40 m² [430.6 ft²]	10 - 13 hours	80 m³ [2,825 ft³]			
Awards		n Best Award (US s Choice Award						
Application	Indoor & Outdo	oor			and spin definition of the states			
Surround Colour	Black				Flex 68	Flex 68BY		
Burner Colours Options	Stainless	s Steel	Black					
Materials	Toughened Gla	c Sealed) Hi-tem ass, Grade 304 S otional Black Cer	tainless Steel		Flex 68	Flex 68BY.BXL		
Approx. Weight	68BY.BXL & 68 68BY.BX2 100	3 <b>BY.BXR</b> 95.5kg .2kg [220.4lbs]	[210.1lbs] charcoal, fire screen.			delle stationent des		

Flex 68BY.BXR



Flex 68BY.BX2

\*These values are indicative only and may vary depending on the model purchased, installation, and the seasonal resource used to manufacture e-NRG.

Physical model dimensions should be verified against cut out dimensions BEFORE installation begins to confirm tolerances align.

e-NRG Bioethanol / e-NRG.com

These models comply with existing standards in the USA, Europe, UK and Australia. O-TL listed to UL1370, EN 16647 BSI Certified and ACCC Safety Mandate compliant.

#### FOR MORE INFORMATION PLEASE REFERENCE THE CLEARANCE & INSTALLATION MANUAL

Disclaimer. All product specifications and data are subject to change without notice and believed to be correct at the time of publication. MAD Design Group (MDG), its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "MAD Design Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. MDG disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify MDGs terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of MDG. Customers using or applications. Images are indicative only.


Fuel Type

### Flex 68BY

Physical model dimensions should be verified against cut out dimensions BEFORE installation begins to confirm tolerances align.

ESF.FX.68BY (Flame only) [6.9] [31.8] [5.1] 175 807 

[71.4]  ecosmar+<sup>™</sup> Fire






ESF.FX.68BY.BXR (Right Decorative Box)

ESF.FX.68BY.BX2 (Left & Right Decorative Box)

Side View

[71.4] [30.3] [30



FOR MORE INFORMATION PLEASE REFERENCE THE CLEARANCE & INSTALLATION MANUAL

Disclaimer. All product specifications and data are subject to change without notice and believed to be correct at the time of publication. MAD Design Group (MDG), its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "MAD Design Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. MDG disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify MDGs terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of MDG. Customers using or applications. Images are indicative only.