

Pure 2400W specifications



Heatscope® Pure 2400W SKU HTS.1.PUR.24.WH HTS.1.PUR.24.BL MPN MHS-PE2400WT.100 MHS-PE2400AB.100 Colours White Black Dimensions (L x W x H) 1044 x 166 x 87 mm Weight (approx) 7.5kg Electrical Connection 220 - 240V AC~, 50/60 Hz, 10.43A Heat Output 2400W / 8,190 BTU/h IP Standard IP65 Full Heat 20-30 sec. Visible Light < 300-400 Lumen			
MPN MHS-PE2400WT.100 MHS-PE2400AB.100 Colours White Black Dimensions (L x W x H) 1044 x 166 x 87 mm Weight (approx) 7.5kg Electrical Connection 220 - 240V AC~, 50/60 Hz, 10.43A Heat Output 2400W / 8,190 BTU/h IP Standard IP65 Full Heat 20-30 sec. Visible Light < 300-400 Lumen		Heatscope® Pure 2400W	
Colours White Black Dimensions (L x W x H) 1044 x 166 x 87 mm Weight (approx) 7.5kg Electrical Connection 220 - 240V AC~, 50/60 Hz, 10.43A Heat Output 1PStandard IP65 Full Heat 20-30 sec. Visible Light < 300-400 Lumen Included Accessories Bracket for wall or ceiling mounting Optional Accessories Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	SKU	HTS.1.PUR.24.WH	HTS.1.PUR.24.BL
Dimensions (L x W x H) Weight (approx) 7.5kg Electrical Connection 220 - 240V AC~, 50/60 Hz, 10.43A Heat Output 1P Standard IP65 Full Heat 20-30 sec. Visible Light Included Accessories Bracket for wall or ceiling mounting Optional Accessories Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	MPN	MHS-PE2400WT.100	MHS-PE2400AB.100
Weight (approx) Flectrical Connection 220 - 240V AC~, 50/60 Hz, 10.43A Heat Output 1P Standard IP65 Full Heat 20-30 sec. Visible Light Included Accessories Optional Accessories Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	Colours	White	Black
Electrical Connection 220 - 240V AC~, 50/60 Hz, 10.43A Heat Output 2400W / 8,190 BTU/h IP Standard IP65 Full Heat 20-30 sec. Visible Light < 300-400 Lumen Included Accessories Bracket for wall or ceiling mounting Optional Accessories Extension Rods Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	Dimensions (L x W x H)	1044 x 166 x 87 mm	
Heat Output IP Standard IP65 Full Heat 20-30 sec. Visible Light Included Accessories Optional Accessories Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	Weight (approx)	7.5kg	
IP Standard IP65 Full Heat 20-30 sec. Visible Light < 300-400 Lumen Included Accessories Bracket for wall or ceiling mounting Optional Accessories Extension Rods Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	Electrical Connection	220 - 240V AC~, 50/60 Hz, 10.43A	
Full Heat 20-30 sec. Visible Light < 300-400 Lumen Included Accessories Bracket for wall or ceiling mounting Optional Accessories Extension Rods Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	Heat Output	2400W / 8,190 BTU/h	
Visible Light < 300-400 Lumen Included Accessories Bracket for wall or ceiling mounting Optional Accessories Extension Rods Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	IP Standard	IP65	
Included Accessories Bracket for wall or ceiling mounting Optional Accessories Extension Rods Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	Full Heat	20-30 sec.	
Optional Accessories Extension Rods Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	Visible Light	< 300-400 Lumen	
Compatibility Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control),	Included Accessories	Bracket for wall or ceiling mounting	
	Optional Accessories	Extension Rods	
Zigbee Motion Sensor (extra parts required)	Compatibility	Dual WiFi Smart Switch (w/ App), ZigBee Wireless Switch (Remote Control), ZigBee Motion Sensor (extra parts required)	





3.9 x 2.8 m / 12.8 x 9.2 ft

Disclaimer. All product specifications and data are subject to change without notice and believed to be correct at the time of publication. MAD Design Group (MDG), its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "MAD Design Group"), disclaim any and all liability or any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. MDG disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify MDGs terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of MDG. Customers using or selling MDG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify MDG for any damages arising or resulting from such use or sale. Please contact authorised personnel from MDG to obtain written terms and conditions regarding products designed for such applications. Images are indicative only.

^{*}Values are approximate. Max. temperature increases achievable in enclosed spaces at 16°C (dependent on the respective installation conditions and mounting height).